

Standard Construction DETAILS

EXTERIOR FEATURES

Foundation Walls: Front Foundation Covering: Foundation Footer Drains: Concrete Floor: Garage Floor: Basement Windows: Exterior Walls Framing: Siding: Fascia & Soffits: **Gutters & Downspouts:** Shutters: Roof: Shingles: **Roof Venting: Standard Windows: Exterior Front Door: Exit Door: Overhead Garage Doors:** Porches and/or Stoops: **Basement Egress:**

Poured Concrete Walls, 8' tall, brick pattern reinforced & damp proofed, as per code 8" Brick Veneer on front foundation wall Drain tile around foundation, extended to grade; or sump pump 4" Concrete Slab over 6 mil. Poly on 4" gravel base Engineered and Certified; 4" Concrete Slab w/rebar Vinyl sliding Basement Sashes; location per plan Walls 2" x 6" Wood Studs @ 24" O.C.; 7/16" O.S.B. Sheathing; Whole House wrap Certainteed Mainstreet Vinyl Dutch Lap; double 5" exposure, woodgrain Aluminum Fascia & Vinyl Soffit 5" Seamless Aluminum Gutters and Downspouts Mid-America Vinyl Panel Style, per plan Engineered Roof Truss System, 7/16" O.S.B. Sheathing Tamko Limited Lifetime Architectural Fiberglass w/synthetic Felt and Drip Edge Continuous Roof Ridge Venting Simonton Single Hung Vinyl Windows; Low-E Glass w/Grills between Glass/Screens Fiberglass insulated, "Colonial" style, Six-Panel; Door Sidelights, as per plan Simonton Vinyl Sliding glass patio door w/screen, per plan Steel Panel w/baked-on enamel white finish Front Porch, as per plan; Concrete Stoop at other Exit Doors, as per plan Sliding egress window w/window well or standard egress windows

CONSTRUCTION FEATURES

3/4" T & G, O.S.B. Subfloor, glued & nailed over Joists
Pine box stairs, carpeted on main level
w/ Oak Colonial Railing & Balusters, natural finish
Unfinished Pine Box Stairs, with handrail
2"x4" studs at 16" O.C.
2"x4" studs at 24" O.C. for Non-Load Bearing Walls
½" Gypsum Board and water resistant board in tub/shower areas;
Drywall on garage ceiling - unfinished
Latex, flat, two coats on Walls & Ceilings; Semi-Gloss on Doors and Trim
Prehung, masonite, "Colonial" style six-panel
Kwikset Locksets; Brushed Nickel, keyed alike
2-1/4" Beaded edge casing, fingerjoint & 3" Beaded base; painted

PLUMBING FEATURES

Water Piping/Hse Drain/Vents: Water Piping-CPVC; House Drains & Vents-PVC Water Heater: 50 gallon Electric High-Recovery, located in Basement as per plan **Exterior Hose Bibs:** Two, located front and rear as per plan with interior shut-offs. **Kitchen Sink:** Self Rimming, stainless steel, double bowl Sink w/American Standard, Chrome single lever faucet and sprayer American Standard, single lever; chrome finish or nickel **Bath Faucets: Bath Tubs and Showers:** Aker/Maxx Tub-Shower, Gelcoat Fiberglass units- white **Soaking Tubs:** Aker/Maxx, Gelcoat Fiberglass units, as per plan- white Washer/Dryer Hookups: In laundry area, per plans Water line with valve in wall **Icemaker Connection:** Sub Slab Ventilation: Passive Radon Mitigation Vent installed; terminated through roof

Subflooring: Main Stairs and Railing:

Basement Stairs & amp; Railing: Load-Bearing Walls: Interior Wall Partitions: Drywall:

Painting: Interior Doors: Door Hardware: Interior Trim:

HEATING & VENTILATION FEATURES

Heating & Cooling System: Ventilation: High-Efficiency, 14 SEER minimum, Heat Pump System w/steel duct supply lines Bath Fans, Range Hood or Over-Range Microwave & Dryers- vented to exterior

ELECTRICAL FEATURES

Service: Exterior Outlets: Telephone & Cable: Doorbell and Chime: Lighting Fixtures: Smoke & CO Detectors: Exterior Lighting: Minimum 200 amp Service Panel Minimum (2) GFI outlets, located at front and rear of house Total of (1) Phone Jack (4) Cable TV Jacks (Cat-5 phone wire & RG-6 cable wire) Front Door Selected Light Packages Per Local Codes – Electric with battery back-up Fixtures at all Exit Doors, per plan

INSULATION FEATURES

Exterior Framed Walls: Basement Walls: Ceilings: Air Sealant: Batt Insulation with R-21 rating on 2"x6" walls- heated living space Blanket insulation with facing below grade with R-11 rating Minimum R-49 Blown fiber insulation, per local codes Air seal all exterior panel joints, window and door jambs; electric and plumbing penetrations

FLOOR FINISH FEATURES

Kitchen and Baths: Carpeted Areas: Armstrong No-Wax Vinyl Flooring, as per plan Shaw Carpet w/6 lb. Padding

CLOSET SYSTEMS & BATH ACCESSORIES FEATURES

Closet & Pantries: Baths: Coated Wire Shelving and Hanger System in all closets and pantries as per plan Chrome or Nickel finish Towel Bars and TP Holder and Vanity Mirror

CABINETRY FEATURES

Kitchen Cabinets:

Kitchen Countertop: Bathroom Vanities: Vanity Tops: Quality Woodstar Cabinetry with ¾" adjustable shelving; Maple, White, & Birch finishes; choice of Stain and Hardware Laminated, Self-edge Kitchen Countertops Quality Woodstar Vanities; Maple, White, & Birch finishes; choice of Stain & Hrdw Cultured Marble Vanity Tops with oval integral bowl and backsplash

HOME WARRANTY PROGRAM FEATURES

Quality Builders Warranty:

Quality Builders Warranty: Pre Move-in Home Orientation final inspection conducted by Contractor One-Year Builder Materials/Workmanship Warranty Two-Year Major Component Warranty (HVAC/Electric/Plumbing) Ten-Year Structural Warranty underwritten by QBW

Our Continuing commitment to quality products may mean a change in specifications without notice. *Standards listed above must conform to Local, County, State and National Building Codes and are subject to change. Ask an Oliver Homes' Representative about the specifications used in your County or State Revised 02/2024